


Specifications:

- Current Rating:9.0 AC/DC
- Voltage Rating:600V AC/DC
- Contact Resistance:10m ohm. max.
- Withstanding Voltage:1,500V AC/minute
- Operating Temperature Range:-40°C~+105°C
- Application Wires:AWG16 to 28
- Material and Finish
- Contact:Phosphor Bronze
- Finish:Tin Plated
- Packing:See Table

Part No	Wire Apply	A	B	C	D	Q'ty/Reel
4281F1618-99	16-18AWG	3.6	4.5	2.3	2.7	4,000Pcs
4281F1822-99	18-22AWG	3.6	4.5	1.9	2.3	4,000Pcs
4281F2428-99	24-28AWG	2.3	2.3	1.8	1.65	5,000Pcs

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	CnC Tech Industrial Cable and Connector Technology		SIZE A4	D
				UNIT: MM	DESCRIPTION: FEMALE TERMINAL MATES W/MALE HOUSING 4282 SERIES,PHOSPHOR BRONZE, CRIMP TIN				
				SCALE:1:1					
				APPROVAL:	SHEET: 1 / 2	PART NO: 4281F-XXXX-99			
REV	DATE	FILE	BY		PROJECTION: 				

1

2


3

4


5

Front View


(A)





Back View



(B)




(C)




Part No	Q'ty/Reel	Reel/Carton	Q'ty/Carton
4281F1618-99	4,000PCS	6Reel	24,000PCS
4281F1822-99	4,000PCS	6Reel	24,000PCS
4281F2428-99	5,000PCS	6Reel	30,000PCS

Package Quantity

(E)



(D)



Note :

A.Reel packing Size: $\phi 560 \times 25$, A=A, T=5mm; Paper shaft Size: $\phi 100 \times 22$, T=8mm

B.Direction all the same as (Picture B), only available after plating, separate each layer of terminal by putting paper between it.

C.Put styrofoam inside to avoid defective terminal, attach label on each tray then place into PE bag.

D.Seal carton and attach carton label

RoHS Compliant

				DRAWN:	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	CnC Tech Industrial Cable and Connector Technology		SIZE A4
				APPROVAL:	SCALE:1:1	PART NO: 4281F-XXXX-99		
					SHEET: 2 / 2			
REV	DATE	FILE	BY		PROJECTION:			