

ET

RoHS RoHS Compliant



Introduction

The ET series is Copal's standard size high capacity toggle switch. The ET series are available in various current rating, switching functions, and terminals. The housing is made of self-extinguishing phenol resin which has excellent heat resistance, arc resistance, and tracking resistance. The contacts are designed to eliminate chattering and bouncing to prevent insulation deterioration.

Part Numbering

E	T	2	25	K	12	-	Z
Series code	Actuator shape	No. of poles	Current	Switching function	Terminal styles		

Fig.	No. of poles
1	1pole
2	2poles
3	3poles
4	4poles
6	6poles

Fig.	AC125V	AC250V
03	3A	—
05	5A	3A
06	6A	(2A)
10	10A	(7A)

Fig.	AC125V	AC250V
15	15A	10A
20	20A	12A
25	25A	15A
30	30A	(25A)

Fig.	Terminal style
None	TAB#250
10	Screw Terminal
12	Solder Terminal
13	Plate Connect SolderTerminal

1pole 3pole	2pole 4pole 6pole	Key way	Key way	Key way
A	K	ON	—	OFF
C	M	OFF	—	(ON)
D•V	N	ON	—	ON
E	P	ON	OFF	ON
F	R	ON	—	(ON)
G	S	(ON)	OFF	(ON)
H	—	ON	OFF	(ON)
—	PA	ON	ON	OFF











Terminal Style and Dimentions










TAB#250 (Style:—)	Screw Terminal (Style:10)			Solder Terminal	
	M3.5×0.6	M4×0.7	M4.5×0.75	Solder Terminal (Style:12•13)	Style:12 ET103□12 ET206□12 Type
	ET115•215Type	ET120•220Type	ET125•225•230Type		

(ON) and (OFF) : Momentary.

Please refer to P.564 for Common Specifications

ET Series Selection Table

Part No.	Appearance	No. of poles	Rating	Switching function	Terminal style	Page
ET103		1	AC125V 3A	ON - OFF ON - ON	Solder Terminal  t=0.25	416
ET105		1	AC125V 5A AC250V 3A	ON - OFF ON - ON ON - OFF - ON	Solder Terminal  t=0.7	416
ET205		2				418
ET110		1	AC125V 10A AC250V 7A	ON - OFF ON - ON ON - OFF - ON ON - (ON) ON - OFF - (ON)	TAB # 250  t=0.8	417
ET210		2			Screw Terminal (M3.5×0.6)  t=1	419
ET115		1	AC125V 15A AC250V 10A	ON - OFF OFF - (ON) ON - ON ON - OFF - ON (ON) - OFF - (ON) ON - OFF - (ON)	Solder Terminal  t=0.7	417
ET215		2				419
ET315		3			Solder Terminal  t=0.7	421
ET415		4				
ET120		1	AC125V 20A AC250V 12A	ON - OFF ON - ON	TAB # 250  t=0.8	417
ET125		1	AC125V 25A AC250V 15A	ON - OFF ON - ON ON - OFF - ON	Screw Terminal (M4.5×0.6)  t=1.6	418
ET225		2			Solder Terminal  t=0.8	420

Part No.	Appearance	No. of poles	Rating	Switching function	Terminal style	Page
ET425		4	AC125V 25A AC250V 15A	ON - OFF ON - ON	Solder Terminal 	424
ET206		2	AC125V 6A	ON - OFF	Solder Terminal 	418
			AC125V 6A AC250V 2A	ON - ON		
ET220		2	AC125V 20A AC250V 12A	ON - OFF ON - ON (ON) - OFF - (ON)	Solder Terminal	420
ET230		2	AC125V 30A AC250V 25A	ON - OFF ON - ON ON - OFF - ON	Screw Terminal (M4.5×0.75) 	420
ET330		3			Solder Terminal 	422
ET310		3	AC125V 10A AC250V 7A	ON - OFF ON - ON ON - OFF - ON	Solder Terminal	421
ET410		4				422
ET420		4	AC125V 20A AC250V 12A	ON - ON	Solder Terminal 	423
ET420 Plate type						424
ET610N Plate type		6	AC125V 10A AC250V 7A	ON - ON		424
ET620N Plate type		6	AC125V 20A AC250V 12A	ON - ON		425

● Ratings are based on resistance load.


● Refer to P.425 for UL-recognized and CSA, PSE-certified products.

(ON) and (OFF) : Momentary.


Panel Cut-Out Dimensions

● Refer to P.426 for a list of accessories.

Panel thickness : 5.5mm max.





With Locking Ring



Without Locking Ring

Note : Panel thickness should be 5.5 mm max. unless otherwise specified.

ET103□12 (1 pole)



Terminal numbers are shown on the bottom of the switch.

Switching function	Key way	Key way	Key way
Part No.			
ET103A12-Z	ON	—	OFF
Connecting terminals	1-4	—	—
★ ET103V12-Z	ON	—	ON
Connecting terminals	1-4	—	3-6




Terminal pins No.3 and No.6 are not available in switches with Switching Function "A".

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET103A12	AC125V 3A	30mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	10,000回 cycles
ET103V12					

ET105□12 (1 pole)

Terminal pin No.2 is not available in switches with Switching Function "A".



Terminal numbers are shown on the bottom of the switch.

L dimensions

Part No.	Terminal style	Solder Terminal
ET105A12-Z		24.6±1
ET105D12-Z		24.6±1
ET105E12-Z		24.6±1


Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET105A12	AC125V 5A AC250V 3A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000回 cycles
ET105D12					
ET105E12					

Switching function	Key way	Key way	Key way
Part No.			
☆ ET105A12-Z	ON	—	OFF
Connecting terminals	1-3	—	—
☆ ET105D12-Z	ON	—	ON
☆ ET105E12-Z	ON	OFF	ON
Connecting terminals	2-3	—	2-1

ET110 (1 pole)

Terminal pin No.2 is not available in switches with Switching Function "A".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET110A■	AC125V 10A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	30,000 cycles
ET110D■	AC250V 7A				20,000 cycles
ET110E■	AC250V 7A				
ET110F■	AC125V 10A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET110H■	AC250V 7A				

L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET110A■-D■-Z		—	—	24.6 ^{±1}
ET110E■-Z		—	—	24.6 ^{±1}
ET110F■-Z		27.6 ^{±1}	—	24.6 ^{±1}
ET110H■-Z		27.6 ^{±1}	25.4 ^{±1}	24.6 ^{±1}

Part No.	Switching function	Key way	Key way	Key way
ET110A■-Z		ON	—	OFF
Connecting terminals		1-3	—	—
ET110D■-Z		ON	—	ON
ET110E■-Z		ON	OFF	ON
ET110F■-Z		ON	—	(ON)
ET110H■-Z		ON	OFF	(ON)
Connecting terminals		2-3	—	2-1

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

ET115 (1 pole)

Terminal pin No.2 is not available in switches with Switching Function "A", "B", or "C".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET115A■	AC125V 15A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	30,000 cycles
ET115D■	AC250V 10A				20,000 cycles
ET115E■	AC250V 10A				
ET115C■	AC125V 15A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET115G■	AC250V 10A				20,000 cycles
ET115H■	AC250V 10A				

L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET115A■-D■-Z		27.6 ^{±1}	25.4 ^{±1}	24.6 ^{±1}
ET115E■-Z		27.6 ^{±1}	25.4 ^{±1}	24.6 ^{±1}
ET115C■-F~H■-Z		—	25.4 ^{±1}	24.6 ^{±1}

Part No.	Switching function	Key way	Key way	Key way
ET115A■-Z		ON	—	OFF
Connecting terminals		1-3	—	—
ET115C■-Z		OFF	—	(ON)
Connecting terminals		—	—	1-3
ET115D■-Z		ON	—	ON
ET115E■-Z		ON	OFF	ON
ET115G■-Z		(ON)	OFF	(ON)
ET115H■-Z		ON	OFF	(ON)
Connecting terminals		2-3	—	2-1

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

ET120 (2 pole)

Terminal pin No.2 is not available in switches with Switching Function "A".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET120A■	AC125V 20A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET120D■	AC250V 12A				

L dimensions

Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET120A■-D■-Z		—	—	24.6 ^{±1}

Part No.	Switching function	Key way	Key way	Key way
ET120A■-Z		ON	—	OFF
Connecting terminals		1-3	—	—
ET120D■-Z		ON	—	ON
Connecting terminals		2-3	—	2-1


■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

(ON) : Momentary.

■ shows the terminal style "A", "B", or "C".

ET125 (1 pole)

Terminal pin No.2 is not available in switches with Switching Function "A".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating	Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET125A ET125D	AC125V 25A AC250V 15A (DC2V 100mA)	20mΩ Max. 1minute	AC1500V 100MΩ Min. (DC500V)	20,000 cycles

L dimensions


Part No.	Terminal style	TAB#250	Screw Terminal	Solder Terminal
ET125A -Z ET125D -Z		27.6±1	28.8±1	24.6±1

Part No.	Switching function	Key way	Key way	Key way
ET125A -Z	ON	—	—	OFF
Connecting terminals	1-3	—	—	—
ET125D -Z	ON	—	—	ON
Connecting terminals	2-3	—	—	2-1

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

ET205 (2 poles)

Terminal pins No.2 and No.5 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.


Specifications

Rating	Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET205K12 ET205N12 ET205P12	AC125V 5A AC250V 3A (DC2V 100mA)	20mΩ Max. 1minute	AC1500V 100MΩ Min. (DC500V)	20,000 cycles

Part No.	Switching function	Key way	Key way	Key way
★ ET205K12-Z	ON	—	—	OFF
Connecting terminals	1-3 4-6	—	—	—
★ ET205N12-Z	ON	—	—	ON
★ ET205P12-Z	ON	OFF	—	ON
Connecting terminals	2-3 5-6	—	—	2-1 5-4

ET206□12 (2 poles)

Terminal pins No.3 and No.6 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.


Specifications

Rating	Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET206K12	AC125V 6A (DC2V 100mA)	20mΩ Max. 1minute	AC1500V 100MΩ Min. (DC500V)	10,000 cycles
ET206N12	AC125V 6A AC250V 2A			

Part No.	Switching function	Key way	Key way	Key way
★ ET206K12-Z	ON	—	—	OFF
Connecting terminals	2-1 5-4	—	—	—
★ ET206N12-Z	ON	—	—	ON
Connecting terminals	2-1 5-4	—	—	2-3 5-6

ET210 (2 poles)

Terminal pins No.2 and No.5 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET210K■	AC125V 10A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	30,000 cycles
ET210N■	AC250V 7A				
ET210P■					
ET210PA12	AC125V 10A				20,000 cycles

L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET210K■-N■-Z		30.6 $\pm$ 1	28.4 $\pm$ 1	27.6 $\pm$ 1
ET210P■-Z		30.6 $\pm$ 1	28.4 $\pm$ 1	27.6 $\pm$ 1
ET210PA12-Z		—	—	27.6 $\pm$ 1

Part No.	Switching function	Key way	Key way	Key way
ET210K■-Z		ON	—	OFF
Connecting terminals		1-3 4-6	—	—
ET210N■-Z		ON	—	ON
ET210P■-Z		ON	OFF	ON
Connecting terminals		2-3 5-6	—	2-1 5-4
★ ET210PA12-Z		ON	ON	OFF
Connecting terminals		2-3 5-6	5-6	—

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.of part numbers.

ET215 (2 poles)

Terminal pins No.2 and No.5 are not available in switches with Switching Function "K", "L", or "M".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET215K■	AC125V 15A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	30,000 cycles
ET215N■	AC250V 10A				
ET215P■					
ET215R■	AC125V 15A				20,000 cycles
ET215S■	AC250V 10A				

L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET215K■-N■-Z		30.6 $\pm$ 1	28.4 $\pm$ 1	27.6 $\pm$ 1
ET215P■-Z		30.6 $\pm$ 1	28.4 $\pm$ 1	27.6 $\pm$ 1
ET215M-R-S ■-Z		—	28.4 $\pm$ 1	27.6 $\pm$ 1

Part No.	Switching function	Key way	Key way	Key way
ET215K■-Z		ON	—	OFF
Connecting terminals		1-3 4-6	—	—
ET215M■-Z		OFF	—	(ON)
Connecting terminals		—	—	1-3 4-6
ET215N■-Z		ON	—	ON
ET215P■-Z		ON	OFF	ON
ET215R■-Z		ON	—	(ON)
ET215S■-Z		(ON)	OFF	(ON)
Connecting terminals		2-3 5-6	—	2-1 5-4

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.of part numbers.

ET220 (2 poles)

Terminal pins No.2 and No.5 are not available in switches with Switching Function "K", "L", or "M".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET220K	AC125V 20A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET220N	AC250V 12A				
ET220S	AC125V 20A AC250V 12A				

L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET220K ■• N ■-Z		—	—	27.6±1
ET220S -Z		30.6±1	31.8±1	27.6±1

Part No.	Switching function	Key way	Key way	Key way
ET220K ■-Z		ON	—	OFF
Connecting terminals	1-3 4-6	—	—	—
ET220N ■-Z		ON	—	ON
ET220S ■-Z		(ON)	OFF	(ON)
Connecting terminals	2-3 5-6	—	—	2-1 5-4

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

ET225 (2 poles)

Terminal pins No.2 and No.5 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET225K	AC125V 25A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET225N	AC250V 15A				
ET225P					

L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET225K ■• N ■-Z ET225P ■-Z		30.6±1	31.8±1	27.6±1

Part No.	Switching function	Key way	Key way	Key way
ET225K ■-Z		ON	—	OFF
Connecting terminals	1-3 4-6	—	—	—
ET225N ■-Z		ON	—	ON
ET225P ■-Z		ON	OFF	ON
Connecting terminals	2-3 5-6	—	—	2-1 5-4

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

ET230 (2 poles)

Terminal pins No.2 and No.5 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET230N10	AC250V 25A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET230P10	AC125V 30A				

Part No.	Switching function	Key way	Key way	Key way
★ ET230N ■-Z		ON	—	ON
★ ET230P ■-Z		ON	OFF	ON
Connecting terminals	2-3 5-6	—	—	2-1 5-4


(ON) : Momentary.

■ shows the terminal style "(blank)", "10", or "12".

★ : Made to order products.

ET310 (3 poles)

Terminal pins No.2, No.5, and No.8 are not available in switches with Switching Function "A".



Terminal numbers are shown on the bottom of the switch.

寸法/L dimensions


Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET310A-Z		34 ± 2		
ET310D-Z		36.4 ± 1	—	29.1 ± 1
ET310E-Z				

Part No.	Switching function	Key way	Key way	Key way
ET310A-Z		ON	—	OFF
Connecting terminals		1-3 4-6 7-9	—	—
ET310D-Z		ON	—	ON
ET310E-Z		ON	OFF	ON
Connecting terminals		2-3 5-6 8-9	—	2-1 5-4 8-7

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.

ET315 $\square$ 12 (3 poles)

Terminal pins No.2, No.5, and No.8 are not available in switches with Switching Function "A".



Terminal numbers are shown on the bottom of the switch.


Part No.	Switching function	Key way	Key way	Key way
★ ET315D12-Z		ON	—	ON
★ ET315E12-Z		ON	OFF	ON
Connecting terminals		2-3 5-6 8-9	—	2-1 5-4 8-7

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET315D12	AC125V 15A	20mΩ Max.	AC1500V	100MΩ Min.	20,000
ET315E12	AC250V 10A	(DC2V 100mA)	1minute	(DC500V)	cycles

ET330□12 (3 poles)

Terminal pins No.2, No.5, and No.8 are not available in switches with Switching Function "A".

**Specifications**


Rating	Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET330A ET330D12 ET330E12	AC125V 30A AC250V 25A (DC2V 100mA)	20mΩ Max. AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles

L dimensions

Part No.	Terminal style	TAB#250	ScrewTerminal	Solder Terminal
ET330A ■-Z		33.9±2		
ET330D12-Z ET330E12-Z		—	—	29.1±1

Part No.	Switching function	Key way	Key way	Key way
ET330A ■-Z		ON	—	OFF
Connecting terminals		1-3 4-6 7-9	—	—
☆ ET330D12-Z		ON	—	ON
★ ET330E12-Z		ON	OFF	ON
Connecting terminals		2-3 5-6 8-9	—	2-1 5-4 8-7

■ : Refer to "Table of Part Numbers" on P.425 for a full list of part numbers.


ET410□12 (4 poles)**Specifications**

Rating	Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET410N12	AC125V 10A AC250V 7A (DC2V 100mA)	20mΩ Max. AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles

Part No.	Switching function	Key way	Key way	Key way
★ ET410N12-Z		ON	—	ON
Connecting terminals		2-3 5-6 8-9 11-12	—	2-1 5-4 8-7 11-10

ET415□12 (4 poles)

Terminal pins No.2, No.5, No.8, and No.11 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.


Switching function	Key way	Key way	Key way
Part No.			
★ET415P12-Z	ON	OFF	ON
Connecting terminals	2-3 5-6 8-9 11-12	—	-1 5-4 8-7 11-10

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET415P12	AC125V 15A AC250V 10A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles

ET420□12 (4 poles)

Terminal pins No.2, No.5, No.8, and No.11 are not available in switches with Switching Function "K".



Terminal numbers are shown on the bottom of the switch.


Switching function	Key way	Key way	Key way
Part No.			
★ET420N12-Z	ON	—	ON
Connecting terminals	2-3 5-6 8-9 11-12	—	2-1 5-4 8-7 11-10

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET420N12	AC125V 20A AC250V 12A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles

ET420□13 (4 poles)

Terminal pins No.2, No.5, No.8, and No.11 are not available in switches with Switching Function "K".




Terminal numbers are shown on the bottom of the switch.

Part No.	Switching function		
	Viewed from part No. and rating marking side		
★ET420N13-Z	ON	—	ON
Connecting terminals	2-3 5-6 8-9 11-12	—	2-1 5-4 8-7 11-10

Panel Cut-Out Dimensions


(Plate mounting type)

**Specifications**

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET420N13	AC125V 20A AC250V 12A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles

ET425□12 (4 poles)

Terminal pins No.2, No.5, No.8, and No.11 are not available in switches with Switching Function "K".




Terminal numbers are shown on the bottom of the switch.

Part No.	Switching function		
	Key way		
★ET425K12-Z	ON	—	OFF
Connecting terminals	1-3 4-6 7-9 10-12	—	—
★ET425N12-Z	ON	—	ON
Connecting terminals	2-3 5-6 8-9 11-12	—	2-1 5-4 8-7 11-10

Specifications

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET425K12	AC125V 25A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	20,000 cycles
ET425N12	AC250V 15A				


ET610N13 (6 poles)

Terminal numbers are shown on the bottom of the switch.




Part No.	Switching function		
	Viewed from part No. and rating marking side		
☆ET610N13-Z	ON	—	ON
Connecting terminals	2-3 5-6 8-9 11-12 14-15 17-18	—	2-1 5-4 8-7 11-10 14-13 17-16

Panel Cut-Out Dimensions


(Plate mounting type)

**Specifications**

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET610N13	AC125V 10A AC250V 7A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	5,000 cycles

ET620N13 (6 poles)

Part No. & rating marking side




Terminal numbers are shown on the bottom of the switch.

Switching function	Viewed from part No. and rating marking side		
Part No.	★ET620N13-Z	—	ON
Connecting terminals	2-3 5-6	—	2-1 5-4
	8-9 11-12	—	8-7 11-10
	14-15 17-18	—	14-13 17-16

Panel Cut-Out Dimensions**Specifications**

Rating		Initial contact resistance	Dielectric strength	Insulation resistance	Electrical life
ET620N13	AC125V 20A	20mΩ Max. (DC2V 100mA)	AC1500V 1minute	100MΩ Min. (DC500V)	5,000 cycles
	AC250V 12A				

(Plate mounting type)

**Table of Part Numbers**





	Part No.	※1.	Part No.	※1.	Part No.	※1.	Part No.	※1.
TAB terminals	★ ET110F-Z		★ ET115D-Z		★ ET215N-Z	40.0	★ ET225P-Z	
	★ ET110H-Z		★ ET125A-Z	26.6	☆ ET215P-Z	39.7	★ ET330A-Z	
	ET115A-Z	29.4	★ ET215K-Z	39.3	☆ ET225K-Z	39.4		
Screw terminals	☆ ET115A10-Z		★ ET125A10-Z		☆ ET215N10-Z		★ ET230N10-Z	54.4
	★ ET115D10-Z		★ ET215K10-Z		★ ET215P10-Z		★ ET230P10-Z	
Solder terminals	ET103A12-Z	21.0	☆ ET120A12-Z		★ ET215M12-Z		★ ET315D12-Z	54.7
	★ ET103V12-Z	21.0	★ ET120D12-Z		☆ ET215N12-Z	38.1	★ ET315E12-Z	
	☆ ET105A12-Z		☆ ET125A12-Z	25.9	★ ET215P12-Z	37.8	★ ET330A12-Z	
	☆ ET105D12-Z	25.8	★ ET125D12-Z	26.0	★ ET215R12-Z		☆ ET330D12-Z	54.2
	☆ ET105E12-Z		★ ET205K12-Z		ET215S12-Z	38.4	★ ET330E12-Z	
	☆ ET110A12-Z	25.8	★ ET205N12-Z		★ ET220K12-Z		★ ET410N12-Z	57.4
	☆ ET110D12-Z		★ ET205P12-Z		★ ET220N12-Z		★ ET415P12-Z	
	★ ET110E12-Z		ET206K12-Z	26.1	★ ET220S12-Z		★ ET420N12-Z	
	ET115A12-Z	25.9	☆ ET206N12-Z	26.3	☆ ET225K12-Z	38.1	★ ET420N13-Z	
	★ ET115C12-Z		☆ ET210K12-Z		ET225N12-Z	38.6	★ ET425K12-Z	
	ET115D12-Z	25.9	☆ ET210N12-Z	38.0	ET225P12-Z		★ ET425N12-Z	
	★ ET115E12-Z	25.9	☆ ET210P12-Z	37.9	★ ET310A12-Z	54.0	☆ ET610N13-Z	105.0
	★ ET115G12-Z		★ ET210PA12-Z		☆ ET310D12-Z	54.6	★ ET620N13-Z	
	★ ET115H12-Z	25.0	☆ ET215K12-Z	37.9	☆ ET310E12-Z		—	—

As shown in the above table, not all products are UL-recognized or CSA-certified. Please check with your local sales representative if you have any questions.






Note: For overseas standards, see P.627.

※1 : Switch mass (g) : includes accessories = hex nut, locking ring, lock washer and terminal screw

■ Standard Accessories ——— 《Supplied with switch》

Part Name	Hex Nut	Hex Nut	Lockwasher	Locking Ring
Part No.	140008010235	140008010221	140008030055	140008020065
Dimensions				
Finish	Nickel plated	Zinc plated	Zinc plated	Zinc plated

■ Optional Accessories ——— 《Supplied separately》

Type	ET-8B		ET	ET	
Part Name	Plate	Plate	Waterproof boot	Boot	Bushing
Part No.	140008040021	140008040025	Red 140000610335 Gray 140000610334 Black 140000610333	140000610080	140008010244
Dimensions					

■ Handling Precautions

1. Soldering Specifications

(1) Manual Soldering

Device : Soldering iron
420°C, Max.; 3 seconds, Max.

(2) Waterproof boot

- ① The boot is fixed to the switch with the built-in screw.
- ② The boot cannot be used for plate-mounting switches.

2. Flux Cleaning

- (1) Solvent : Fluorine or Alcohol type.
- (2) The ET series are not washable. To wash the PC board, clean the soldering surface of the PC board with a brush so that the switch is not exposed to the cleaning solution.

■ Packaging Specification

