

Molding Power Inductors

THTFA1006 Series

TOP-EMC

Features

- Small size ,High current and very low loss
- Ultra low buzz noise, due to composite construction
- RoHS, Halogen Free and REACH Compliance
- Soft saturation characteristic to withstand high current spikes
- High reliability-Reliability tests comply with AEC-Q200



Applications

- DC/DC converters
- Car Navigation Systems
- Battery powered devices
- Meters/Alarms
- PDA/notebook/desktop devices

Product Identification

THTFA
①

1006
②

D
③

1R0
④

M
⑤

T
⑥


- ① Type : THTFA
- ② External Dimensions (L×H) [mm]= 1006
- ③ Feature Type : Differential
- ④ Nominal Inductance : 1R0=1.0μH
- ⑤ Inductance Tolerance : K=±10%
M=±20%
N=±30%
- ⑥ Packing T=Tape Carrier Package

Specifications


Part Number	Inductance (μH) $\pm 20\%$ 1MHz/0.1V	DCR (m Ω) Max.	I sat (A)Typ.	I rms (A)Typ.
THTFA1006D1R0MT	1.0	1.90	50.0	30.0
THTFA1006D1R2MT	1.2	2.20	49.0	29.0
THTFA1006D1R5MT	1.5	2.20	42.0	29.0
THTFA1006D2R2MT	2.2	4.00	32.0	24.0
THTFA1006D3R3MT	3.3	5.60	26.0	19.0
THTFA1006D4R7MT	4.7	7.30	25.0	17.2

- (1) I sat Current: DC current (A) that will cause L0 to drop approximately 30 %
- (2) I rms : DC current (A) that will cause an approximate ΔT of 40 °C (reference ambient temperature is 25°C)
- (3) Operating Temperature: -40°C up to +125°C
- (4) Absolute maximum voltage: DC 60V

Shape And Dimensions



Recommended Pattern




Dimensions In mm

SYM	A	B	C	D	E	F	H	I	J
DIM	11.3	10.0	6.0	8.0	2.2	4.45	6.65	2.6	9.0
TOLE	± 0.5	± 0.5	Max	Typ	± 0.2	± 0.3	Typ	Typ	Typ

Recommended Soldering Technologies

Reflow Condition		Pb-Free Assembly (see as below)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150°C
	-Temperature Max($T_{s(max)}$)	+200°C
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3°C/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature(T_L) (Liquid us)	+217°C
	-Temperature(t_L)	60-90 secs .
Peak Temp (T_P)		+260(+0/-5)°C
Time within 5°C of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp (T_P)		8 min. Max
Do not exceed		+260°C



CONTACT INFORMATION

SHENZHEN TOP-FLIGHT TECHNOLOGY CO.,LTD

4th Floor, C Building, Yuanfen Industrial Park , Bulong Road, Longhua New District, Shenzhen

Tel: 86-755-82908191 Fax: 86-755-82908701 Email: kang@topleve.com

Website: <http://www.topleve.com>